



## FIPS 140-2 Non-Proprietary Security Policy

---

### Symantec NetBackup Cryptographic Module

Software Version 1.0

Document Version 1.0

January 13, 2015

*Prepared For:*



Symantec Corporation  
350 Ellis Street  
Mountain View, CA 9404  
[www.symantec.com](http://www.symantec.com)

*Prepared By:*



SafeLogic Inc.  
530 Lytton Avenue, Suite 200  
Palo Alto, CA 94301  
[www.safelogic.com](http://www.safelogic.com)

## **Abstract**

This document provides a non-proprietary FIPS 140-2 Security Policy for Symantec NetBackup Cryptographic Module.

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	About FIPS 140	5
1.2	About this Document	5
1.3	External Resources	5
1.4	Notices	5
1.5	Acronyms	5
<b>2</b>	<b>Symantec NetBackup Cryptographic Module</b>	<b>7</b>
2.1	Cryptographic Module Specification	7
2.1.1	Validation Level Detail	7
2.1.2	Approved Cryptographic Algorithms	7
2.1.3	Non-Approved Cryptographic Algorithms	10
2.2	Module Interfaces	11
2.3	Roles, Services, and Authentication	12
2.3.1	Operator Services and Descriptions	12
2.3.2	Operator Authentication	13
2.4	Physical Security	13
2.5	Operational Environment	14
2.6	Cryptographic Key Management	14
2.6.1	Random Number Generation	16
2.6.2	Key/Critical Security Parameter (CSP) Authorized Access and Use by Role and Service/Function	16
2.6.3	Key/CSP Storage	16
2.6.4	Key/CSP Zeroization	16
2.7	Self-Tests	16
2.7.1	Power-On Self-Tests	17
2.7.2	Conditional Self-Tests	19
2.7.3	Cryptographic Function	19
2.8	Mitigation of Other Attacks	19
<b>3</b>	<b>Guidance and Secure Operation</b>	<b>20</b>
3.1	Crypto Officer Guidance	20
3.1.1	Software Installation	20
3.1.2	Additional Rules of Operation	20
3.2	User Guidance	20
3.2.1	General Guidance	20

## List of Tables

Table 1 – Acronyms and Terms.....	6
Table 2 – Validation Level by FIPS 140-2 Section.....	7
Table 3 – FIPS-Approved Algorithm Certificates.....	9
Table 4 – Logical Interface / Physical Interface Mapping .....	12
Table 5 – Module Services, Roles, and Descriptions.....	13
Table 6 – Module Keys/CSPs.....	16
Table 7 – Power-On Self-Tests.....	18
Table 8 – Conditional Self-Tests.....	19

## List of Figures

Figure 1 – Module Boundary and Interfaces Diagram.....	11
--	----

## 1 Introduction

### 1.1 About FIPS 140

Federal Information Processing Standards Publication 140-2 — Security Requirements for Cryptographic Modules specifies requirements for cryptographic modules to be deployed in a Sensitive but Unclassified environment. The National Institute of Standards and Technology (NIST) and Communications Security Establishment Canada (CSEC) Cryptographic Module Validation Program (CMVP) run the FIPS 140 program. The NVLAP accredits independent testing labs to perform FIPS 140 testing; the CMVP validates modules meeting FIPS 140 validation. *Validated* is the term given to a module that is documented and tested against the FIPS 140 criteria.

More information is available on the CMVP website at <http://csrc.nist.gov/groups/STM/cmvp/index.html>.

### 1.2 About this Document

This non-proprietary Cryptographic Module Security Policy for the NetBackup Cryptographic Module from Symantec provides an overview of the product and a high-level description of how it meets the security requirements of FIPS 140-2. This document contains details on the module's cryptographic keys and critical security parameters. This Security Policy concludes with instructions and guidance on running the module in a FIPS 140-2 mode of operation.

Symantec NetBackup Cryptographic Module may also be referred to as the “module” in this document.

### 1.3 External Resources

The Symantec website ([www.symantec.com](http://www.symantec.com)) contains information on Symantec services and products. The Cryptographic Module Validation Program website contains links to the FIPS 140-2 certificate and Symantec contact information.

### 1.4 Notices

This document may be freely reproduced and distributed in its entirety without modification.

### 1.5 Acronyms

The following table defines acronyms found in this document:

Acronym	Term
AES	Advanced Encryption Standard
ANSI	American National Standards Institute
API	Application Programming Interface
CMVP	Cryptographic Module Validation Program
CO	Crypto Officer
CSEC	Communications Security Establishment Canada
CSP	Critical Security Parameter
DES	Data Encryption Standard
DH	Diffie-Hellman
DSA	Digital Signature Algorithm
EC	Elliptic Curve
EMC	Electromagnetic Compatibility
EMI	Electromagnetic Interference
FCC	Federal Communications Commission
FIPS	Federal Information Processing Standard
GPC	General Purpose Computer
GUI	Graphical User Interface
HMAC	(Keyed-) Hash Message Authentication Code
KAT	Known Answer Test
MAC	Message Authentication Code
MD	Message Digest
NIST	National Institute of Standards and Technology
OS	Operating System
PKCS	Public-Key Cryptography Standards
PRNG	Pseudo Random Number Generator
PSS	Probabilistic Signature Scheme
RNG	Random Number Generator
RSA	Rivest, Shamir, and Adleman
SHA	Secure Hash Algorithm
SSL	Secure Sockets Layer
Triple-DES	Triple Data Encryption Algorithm
TLS	Transport Layer Security
USB	Universal Serial Bus

**Table 1 – Acronyms and Terms**

## 2 Symantec NetBackup Cryptographic Module

### 2.1 Cryptographic Module Specification

The Symantec NetBackup Cryptographic Module provides cryptographic functions for Symantec NetBackup.

The module's logical cryptographic boundary is the shared library files and their integrity check HMAC files. The module is a multi-chip standalone embodiment installed on a General Purpose Device.

All operations of the module occur via calls from host applications and their respective internal daemons/processes. As such there are no untrusted services calling the services of the module.

#### 2.1.1 Validation Level Detail

The following table lists the level of validation for each area in FIPS 140-2:

FIPS 140-2 Section Title	Validation Level
Cryptographic Module Specification	1
Cryptographic Module Ports and Interfaces	1
Roles, Services, and Authentication	1
Finite State Model	1
Physical Security	N/A
Operational Environment	1
Cryptographic Key Management	1
Electromagnetic Interference / Electromagnetic Compatibility	1
Self-Tests	1
Design Assurance	1
Mitigation of Other Attacks	N/A

Table 2 – Validation Level by FIPS 140-2 Section

#### 2.1.2 Approved Cryptographic Algorithms

The module's cryptographic algorithm implementations have received the following certificate numbers from the Cryptographic Algorithm Validation Program:

Algorithm	CAVP Certificate
AES	2273
HMAC-SHA-1, HMAC-SHA-224, HMAC-SHA-256, HMAC-SHA-384, HMAC-SHA-512	1391
<p>DSA, DSA 2 FIPS 186-2 <b>PQR Ver:</b> Sig Ver- 1024-bit</p> <p>F186-4 <b>PQG Gen:</b> 2048 &amp; 3072 (using SHA-2) <b>PQG Ver:</b> 1024, 2048 &amp; 3072 (using SHA-1 and SHA-2) <b>Key Pair:</b> 2048-bit &amp; 3072-bit <b>Sig Gen:</b> 2048-bit &amp; 3072-bit (using SHA-2) <b>Sig Ver:</b> 1024-bit, 2048-bit &amp; 3072-bit (using SHA-1 &amp; SHA-2)</p>	709
<p>ECDSA, ECDSA2 FIPS 186-2 <b>PKG:</b> Curves (P-224, P-256, P-384, P-521, K-233, K-283, K-409, K-571, B-233, B-409 &amp; B-571) <b>PKV:</b> Curves All P, K &amp; B</p> <p>FIPS 186-4 <b>PKG:</b> Curves (P-224, P-256, P-384, P-521, K-233, K-283, K-409, K-571, B-283, B-409 &amp; B-571) <b>PKV:</b> Curves All P, K &amp; B <b>Sig Gen:</b> (P-224, P-256, P-384, P-521, K-233, K-283, K-409, K-571, B-283, B-409 &amp; B-571) (SHA-2) <b>Sig Ver:</b> Curves P-192, P-224, P-256, P-384, P-521, K-163, K-233, K-283, B-163, B-233, B-283, B-409 &amp; B-571 (any SHA size) K-409 &amp; K-571 (SHA-1)</p>	368



<p>RSA (X9.31, PKCS #1.5, PSS)  FIPS 186-2  <b>ANSIX9.31</b>  Key Gen: 2048-bit, 3072-bit &amp; 4096-bit  Sig Gen: 2048-bit, 3072-bit &amp; 4096 bit (any SHA size)  Sig Ver: 1024-bit, 1536-bit, 2048-bit, 3072-bit &amp; 4096-bit (any SHA size)</p> <p><b>PKCS1 V1 5</b>  Sig Gen: 2048-bit, 3072-bit &amp; 4096-bit (any SHA size)  Sig Ver: 1024-bit, 1536-bit, 2048-bit, 3072-bit &amp; 4096-bit (any SHA size)</p> <p><b>PSS</b>  Sig Gen: 2048-bit, 3072-bit &amp; 4096-bit (any SHA size)  Sig Ver: 1024-bit, 1536-bit, 2048-bit, 3072-bit &amp; 4096-bit (any SHA size)</p> <p>FIPS 186-4  <b>ANSIX9.31</b>  Sig Gen: 2048-bit (using SHA-2)  Sig Ver: 1024-bit, 2048-bit, &amp; 3072-bit (any SHA size)</p> <p><b>PKCS1 V1 5</b>  Sig Gen: 2048-bit &amp; 3072-bit (using SHA-2)  Sig Ver: 1024-bit, 2048-bit, &amp; 3072-bit (any SHA size)</p> <p><b>PSS</b>  Sig Gen: 2048-bit &amp; 3072-bit (using SHA-2)  Sig Ver: 1024-bit, 2048-bit, &amp; 3072-bit (any SHA size)</p>	1166
SHA-1, SHA-224, SHA-256, SHA-384, SHA-512	1954
<p>Triple-DES  Note: the use of two-key Triple DES for encryption is restricted through December 31<sup>st</sup>, 2015: the total number of blocks of data encrypted with the same cryptographic key shall not be greater than 2<sup>^</sup>20. After December 31, 2015, two-key Triple DES shall not be used for encryption.</p>	1420
RNG (ANSI X9.31)	1132
SP 800-90 DRBG (Hash_DRBG, HMAC_DRBG, CTR_DRBG, Dual_EC_DRBG)	281
CVL (ECC CDH KAS)	44

Table 3 – FIPS-Approved Algorithm Certificates

### 2.1.3 Non-Approved Cryptographic Algorithms

The module supports the following non-FIPS 140-2 approved but allowed algorithms:

- RSA (key wrapping; key establishment methodology provides between 112 and 256 bits of encryption strength; non-compliant less than 112 bits of encryption strength)
- EC Diffie-Hellman (key agreement; key establishment methodology provides between 112 and 256 bits of encryption strength; non-compliant less than 112 bits of encryption strength)

The following algorithms are disallowed as of January 1, 2014 per the NIST SP 800-131A algorithm transitions:

- FIPS 186-2 DSA (using SHA-1): PQG Gen- 1024-bit  
Key Gen- 1024-bit  
Sig Gen- 1024-bit
- FIPS 186-4 DSA PQG Gen, 1024-bit (any SHA size)  
Key Gen, 1024-bit  
Sig Gen, 1024-bit (any SHA size), 2048-bit & 3072-bit using SHA-1
- FIPS 186-2 RSA **ANSIX9.31**  
Key Gen 1024 & 1536  
  
**ANSIX9.31**  
Sig Gen 1024 & 1536 (any SHA size); 2048, 3072 & 4096 using SHA-1  
  
**PKCSI V1 5**  
Sig Gen 1024 & 1536 (any SHA size); 2048, 3072 & 4096 using SHA-1  
  
**PSS**  
Sig Gen 1024 & 1536 (any SHA size); 2048, 3072 & 4096 using SHA-1
- FIPS 186-4 RSA **ANSIX9.31**  
Sig Gen 1024 using SHA-1  
  
**PKCSI V1 5**  
Sig Gen 1024 using SHA-1  
  
**PSS**  
Sig Gen 1024 using SHA-1

- FIPS 186-2 ECDSA      **PKG: Curves**    P-192, K-163 & B-163  
    **Sig Gen Curves** All P, K & B
- FIPS 196-4 ECDSA      **PKG: Curves**    P-192, K-163 & B-163  
    **Sig Gen Curves** P-224, P-256, P-384, P-521, K-233, K-283, K-409, K-571,  
    B-233, B-283, B-409 & B-571) (using SHA-1)  
    P-192-, K-163 & B-163 (any SHA size)

## 2.2 Module Interfaces

The figure below shows the module’s physical and logical block diagram:




Figure 1 – Module Boundary and Interfaces Diagram

The interfaces (ports) for the physical boundary include the computer keyboard port, mouse port, network port, USB ports, display and power plug. When operational, the module does not transmit any information across these physical ports because it is a software cryptographic module. Therefore, the

module’s interfaces are purely logical and are provided through the Application Programming Interface (API) that a calling daemon can operate. The logical interfaces expose services that applications directly call, and the API provides functions that may be called by a referencing application (see Section 2.3 – Roles, Services, and Authentication for the list of available functions). The module distinguishes between logical interfaces by logically separating the information according to the defined API.

The API provided by the module is mapped onto the FIPS 140- 2 logical interfaces: data input, data output, control input, and status output. Each of the FIPS 140- 2 logical interfaces relates to the module’s callable interface, as follows:

FIPS 140-2 Interface	Logical Interface	Module Physical Interface
Data Input	Input parameters of API function calls	Network Interface
Data Output	Output parameters of API function calls	Network Interface
Control Input	API function calls	Keyboard Interface, Mouse Interface
Status Output	For FIPS mode, function calls returning status information and return codes provided by API function calls.	Display Controller
Power	None	Power Supply

**Table 4 – Logical Interface / Physical Interface Mapping**

As shown in Figure 1 – Module Boundary and Interfaces Diagram and Table 5 – Module Services, Roles, and Descriptions, the output data path is provided by the data interfaces and is logically disconnected from processes performing key generation or zeroization. No key information will be output through the data output interface when the module zeroizes keys.

## 2.3 Roles, Services, and Authentication

The module supports a Crypto Officer and a User role. The module does not support a Maintenance role. The User and Crypto-Officer roles are implicitly assumed by the entity accessing services implemented by the Module.

### 2.3.1 Operator Services and Descriptions

The module supports services that are available to users in the various roles. All of the services are described in detail in the module’s user documentation. The following table shows the services available to the various roles and the access to cryptographic keys and CSPs resulting from services:

Service	Roles	CSP / Algorithm	Permission
Module initialization	Crypto Officer	None	CO: execute
Symmetric encryption/decryption	User	AES Key, Triple-DES <sup>1</sup> Key	User: read/write/execute
Digital signature <sup>2*</sup>	User	RSA Private Key, DSA Private Key	User: read/write/execute
Symmetric key generation	User	AES Key, Triple-DES Key	User: read/write/execute
Asymmetric key generation	User	RSA Private Key, DSA Private Key	User: read/write/execute
Keyed Hash (HMAC)*	User	HMAC Key HMAC SHA-1, HMAC SHA- 224, HMAC SHA-256, HMAC SHA-384, HMAC SHA-512	User: read/write/execute
Message digest (SHS)	User	SHA-1, SHA-224, SHA-256, SHA-384, SHA-512	User: read/write/execute
Random number generation	User	PRNG Seed and Seed Key	User: read/write/execute
Show status	Crypto Officer User	None	User and CO: execute
Self test	User	All CSPs	User: read/execute
Zeroize	Crypto Officer User	All CSPs	CO: read/write/execute

Table 5 – Module Services, Roles, and Descriptions

### 2.3.2 Operator Authentication

As required by FIPS 140-2, there are two roles (a Crypto Officer role and User role) in the module that operators may assume. As allowed by Level 1, the module does not support authentication to access services. As such, there are no applicable authentication policies. Access control policies are implicitly defined by the services available to the roles as specified in Table 5 – Module Services, Roles, and Descriptions.

## 2.4 Physical Security

This section of requirements does not apply to this module. The module is a software-only module and does not implement any physical security mechanisms.

<sup>1</sup> Two-key Triple-DES is restricted and only available for legacy use in accordance with SP800-131A.

<sup>2</sup> Note that per SP800-131A, issuing 1024-bit signatures with SHA-1 is disallowed as of the end of 2013.

\* Indicates non-Approved services if non-Approved key sizes are utilized (<112 bits)

## 2.5 Operational Environment

The module operates on a general purpose computer (GPC) running a general purpose operating system (GPOS). For FIPS purposes, the module is running on this operating system in single user mode and does not require any additional configuration to meet the FIPS requirements.

The module was tested on the following platforms:

- Microsoft Windows Server 2008 R2 on a Dell Optiplex 755
- Red Hat Enterprise Linux 6.3 on a Dell Optiplex 755
- CentOS 6.3 on a Dell Optiplex 755
- SUSE Linux Enterprise 11SP2 on a Dell Optiplex 755

The cryptographic module is also supported on the following operating environments for which operational testing and algorithm testing was not performed:

- HP-UX IA64 11.31 Mar2010
- AIX 5.3 TL12 SP2
- Solaris 10.0 U4 Sparc & U2 x86\_64

Compliance is maintained for other versions of the respective operating system family where the binary is unchanged. No claim can be made as to the correct operation of the module or the security strengths of the generated keys when ported to an operational environment which is not listed on the validation certificate.

The GPC(s) used during testing met Federal Communications Commission (FCC) FCC Electromagnetic Interference (EMI) and Electromagnetic Compatibility (EMC) requirements for business use as defined by 47 Code of Federal Regulations, Part15, Subpart B. FIPS 140-2 validation compliance is maintained when the module is operated on other versions of the GPOS running in single user mode, assuming that the requirements outlined in NIST IG G.5 are met.

## 2.6 Cryptographic Key Management

The table below provides a complete list of Critical Security Parameters used within the module:

Keys and CSPs	Storage Locations	Storage Method	Input Method	Output Method	Zeroization	Access
AES Key	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD

Keys and CSPs	Storage Locations	Storage Method	Input Method	Output Method	Zeroization	Access
Triple-DES Key	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
RSA Public Key	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
RSA Private Key*	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
DSA Public Key	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
DSA Private Key*	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
HMAC Key*	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
PRNG Seed	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
PRNG Seed Key	RAM	Plaintext	API call parameter	None	power cycle cleanse()	CO: RWD U: RWD
Integrity Key	Module Binary	Plaintext	None	None	None	CO: RWD U: RWD
EC DSA Private Key	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DSA Public Key	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DH Public Components	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DH Private Components	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DRBG Entropy	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DRBG S Value (Seed Length)	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
EC DRBG init_seed	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
HMAC DRBG Entropy	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
HMAC DRBG V Value (Seed Length)	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
HMAC DRBG Key	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD
HMAC DRBG init_seed	RAM	Plaintext	None	None	power cycle cleanse()	CO: RWD U: RWD

R = Read W = Write D = Delete

\* Indicates non-Approved services if non-Approved key sizes are utilized (<112 bits)

**Table 6 – Module Keys/CSPs**

The application that uses the module is responsible for appropriate destruction and zeroization of the key material. The module provides functions for key allocation and destruction which overwrite the memory that is occupied by the key information with zeros before it is deallocated.

### **2.6.1 Random Number Generation**

The module uses ANSI X9.31 and DRBG for creation of asymmetric and symmetric keys.

The module accepts input from entropy sources external to the cryptographic boundary for use as seed material for the module's Approved RNGs. This external entropy source provides an estimated minimum amount of 93 bits of entropy, which limits the strength of the generated key.

The module performs continual tests on the random numbers it uses to ensure that the seed and seed key input to the Approved RNG do not have the same value. The module also performs continual tests on the output of the approved RNG to ensure that consecutive random numbers do not repeat.

### **2.6.2 Key/Critical Security Parameter (CSP) Authorized Access and Use by Role and Service/Function**

An authorized application as user (the User role) has access to all key data generated during the operation of the module.

### **2.6.3 Key/CSP Storage**

Public and private keys are provided to the module by the calling process and are destroyed when released by the appropriate API function calls or during power cycle. The module does not perform persistent storage of keys.

### **2.6.4 Key/CSP Zeroization**

The application is responsible for calling the appropriate destruction functions from the API. The destruction functions then overwrite the memory occupied by keys with zeros and deallocates the memory. This occurs during process termination / power cycle. Keys are immediately zeroized upon deallocation, which sufficiently protects the CSPs from compromise.

## **2.7 Self-Tests**

FIPS 140-2 requires that the module perform self-tests to ensure the integrity of the module and the correctness of the cryptographic functionality at start up. In addition some functions require continuous verification of function, such as the random number generator. All of these tests are listed and described in this section. In the event of a self-test error, the module will log the error and will halt. The module must be initialized into memory to resume function.



The following sections discuss the module's self-tests in more detail.

### **2.7.1 Power-On Self-Tests**

Power-on self-tests are executed automatically when the module is loaded into memory. The module verifies the integrity of the runtime executable using a HMAC-SHA1 digest computed at build time. If the fingerprints match, the power-up self-tests are then performed. If the power-up self-test is successful, a flag is set to place the module in FIPS mode.

TYPE	DETAIL
Software Integrity Check	<ul style="list-style-type: none"> <li>• HMAC-SHA1 on all module components</li> </ul>
Known Answer Tests <sup>3</sup>	<ul style="list-style-type: none"> <li>• AES encrypt/decrypt</li> <li>• AES GCM</li> <li>• AES CCM</li> <li>• XTS-AES</li> <li>• AES CMAC</li> <li>• Triple-DES CMAC</li> <li>• ECDH</li> <li>• HMAC-SHA1</li> <li>• HMAC-SHA224</li> <li>• HMAC-SHA256</li> <li>• HMAC-SHA384</li> <li>• HMAC-SHA512</li> <li>• RSA</li> <li>• SHA-1</li> <li>• SHA-224</li> <li>• SHA-256</li> <li>• SHA-384</li> <li>• SHA-512</li> <li>• X9.31 RNG</li> <li>• SP 800-90 DRBG (Hash_DRBG, HMAC_DRBG, CTR_DRBG, Dual_EC_DRBG)</li> <li>• Triple-DES encrypt/decrypt</li> <li>• ECC CDH</li> </ul>
Pair-wise Consistency Tests	<ul style="list-style-type: none"> <li>• DSA</li> <li>• RSA</li> <li>• ECDSA</li> </ul>

Table 7 – Power-On Self-Tests

Input, output, and cryptographic functions cannot be performed while the Module is in a self-test or error state because the module is single-threaded and will not return to the calling application until the power-up self-tests are complete. If the power-up self-tests fail, subsequent calls to the module will also fail - thus no further cryptographic operations are possible.

<sup>3</sup> Note that all SHA-X KATs are tested as part of the respective HMAC SHA-X KAT. SHA-1 is also tested independently.

### 2.7.2 Conditional Self-Tests

The module implements the following conditional self-tests upon key generation, or random number generation (respectively):

TYPE	DETAIL
Pair-wise Consistency Tests	<ul style="list-style-type: none"><li>• DSA</li><li>• RSA</li><li>• ECDSA</li></ul>
Continuous RNG Tests	<ul style="list-style-type: none"><li>• Performed on all approved PRNGs</li></ul>

Table 8 – Conditional Self-Tests

### 2.7.3 Cryptographic Function

The module verifies the integrity of the runtime executable using a HMAC-SHA1 digest which is computed at build time. If this computed HMAC-SHA1 digest matches the stored, known digest, then the power-up self-test (consisting of the algorithm-specific Pairwise Consistency and Known Answer tests) is performed. If any component of the power-up self-test fails, an internal global error flag is set to prevent subsequent invocation of any cryptographic function calls. Any such power-up self-test failure is a hard error that can only be recovered by reinstalling the module<sup>4</sup>. The power-up self-tests may be performed at any time by reloading the module.

No operator intervention is required during the running of the self-tests.

## 2.8 Mitigation of Other Attacks

The Module does not contain additional security mechanisms beyond the requirements for FIPS 140-2 Level 1 cryptographic modules.

---

<sup>4</sup> The initialization function could be re-invoked but such re-invocation does not provide a means from recovering from an integrity test or known answer test failure

## **3 Guidance and Secure Operation**

### **3.1 Crypto Officer Guidance**

#### **3.1.1 Software Installation**

The module is provided directly to solution developers and is not available for direct download to the general public. The module and its host application are to be installed on an operating system specified in Section 2.5 or one where portability is maintained.

#### **3.1.2 Additional Rules of Operation**

1. The writable memory areas of the module (data and stack segments) are accessible only by the application so that the operating system is in "single user" mode, i.e. only the application has access to that instance of the module.
2. The operating system is responsible for multitasking operations so that other processes cannot access the address space of the process containing the module.

### **3.2 User Guidance**

#### **3.2.1 General Guidance**

The module is not distributed as a standalone library and is only used in conjunction with the solution.

The end user of the operating system is also responsible for zeroizing CSPs via wipe/secure delete procedures.

If the module power is lost and restored, the calling application can reset the IV to the last value used.